



VCX-LOOV Lock Open-Only Valve

The VCX-LOOV has been custom engineered to provide a solution for the Department of VA requirement for "Lock Open-Only" valves to be installed on their boiler safety devices.

The VHA Safety Device manual calls for valves on the safety devices to be lockable in the open position only, and must be done so without physically modifying the valve by cutting off a tab or stop. We developed a custom block that is mounted to the valve using the threaded mounting holes built into the valve, and secured it with one way security screws so it cannot be removed once fitted. This is not considered a physical modification to the valve, but is an enhancement utilizing existing features of the valve.

Ordering Information:

Part Number	Description
290-370-0001	1/4" Lock Open-Only Valve
290-370-0002	3/8" Lock Open-Only Valve
290-370-0003	1/2" Lock Open-Only Valve
290-370-0004	3/4" Lock Open-Only Valve
290-370-0005	1" Lock Open-Only Valve
290-370-0006	1.25" Lock Open-Only Valve
290-370-0007	2" Lock Open-Only Valve

Providing a cleaner installation and solution over the current practice of using a wire thru the handle and lock, our LOOV will not only present a professional look to the installation, but it will save time and money when installing....



Features:

- Two-Piece Body
- Reinforced Seats
- Blow-out proof stem design
- Adjustable packing gland
- Full port for full flow & min pressure drop
- Female NPT thread
- 600 CWP (psig)
- 150 psig Saturated Steam



Corporate Offices
3130 Seminole Rd.
Fort Pierce, FL 34951
Ph: 772.468.0053

Combustion Controls Division
2802 Brookdale Ave.
Cleveland, OH 44134
Ph: 216.849.9602